



REVISION RECORD				
REV	ECO	DESCRIPTION	DRPT	DATE
1		增加UL刻字	CSX	10/06/06
2		焊脚由黄铜变更为紫铜	CSX	10/26/06
3		图面更新	YeJ	05/11/07
4		品名、料号增加环保标示“(H)”	CSX	12/10/07
5		图面更新	LJH	04/19/08
6		修改刻字	HD	10/20/08

- Notes:
1. Pitch:10.16mm ,Poles:2-XXP
  2. Rated voltage/current:UL 300V/52A VDE 750V/57A
  3. Operation temperatures:-40℃~+105℃
  4. Withstanding Voltage:AC2000V/1Min
  5. Insulation Resistance:5000MΩ/DC1000V
  6. Wire Range:20~6AWG, 10mm²
  7. Max. Torque Value:M4, 12.24kgf.cm
  8. Undimensioned Tolerances:

Pitch range in mm			Nominal dimension range in mm						
	over 6 to 10	over 10 to 24	over 30 to 60	over 60 to 100	over 100 to 150				
to 6	to 10	to 24	to 30	to 60	to 100	to 150			
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10	

5	DG135T- Pin header	4010B00020 (H)	XX	Pure copper	SnCe
4	DG135T- Cage	X000000920 (H)	XX	Brass	Ni Plated
3	DG135T- Screw	S000001520 (H)	XX	Steel	Cr <sup>3+</sup> Zn
2	DG135T-10.16-00A Cover	4010C0YXXA (H)	1	PBT	UL94V-0
1	DG135T-10.16-00A Housing	4010A0YXXA (H)	1	PBT	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
<div><div><div>DEGSON</div><div>DEGSON ELECTRONICS CO., LTD</div></div><div>NAME</div><div>DG135T-10.16-XXP-1Y-00A (H)</div><div>DRAWING NO. DG135T-10.16-E01</div><div>/PART NO.</div><div>DO NOT SCALE DRAWING</div><div>SHEET 1 OF 1</div></div> <div><div>DATE 10/11/06</div><div>CHD</div><div>DATE</div><div>MFO</div><div>DATE</div><div>APPL</div><div>DATE</div><div>MATERIAL :</div><div>G. E :</div><div>FINISH :</div><div>SCALE : 1:1</div></div> <div><div>THIRD ANGLE PROJECTION</div></div>					
SIZE A3 REV T6 10/20/08					