




SECTION A-A

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
△		Drawing Revise	Haoyh	05/29/06
△		增加UL刻字	CSX	06/19/07
△		增加VDE、CE刻字	CSX	10/27/07
△		更换公差表	LJH	12/15/07
△		图面更新	LJH	05/02/08
△		VDE额定电流由20A改为22A	Zengy	08/28/08

Notes:

1. Pitch: 5.0mm, Poles: 2-12P
2. Rated voltage/current: UL 300V/15A  
VDE 250V/22A △
3. Operation temperatures: -40℃~+105℃
4. Withstanding Voltage: AC2000V/1Min
5. Insulation Resistance: 5000MΩ/DC1000V
6. Wire Range: 22~12AWG, 0.5~2.5mm<sup>2</sup>
7. Max. Torque Value: M2.5, 4.08kgf.cm
8. Undimensioned Tolerances:

Pitch range in mm			Nominal dimension range in mm						
to	over	to	to	over	over	over	over	over	
6	10	10	24	30	60	100	150		—
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10	—

3	DG167 Screws	S000001530 (H)	XX	Steel	Cr <sup>3+</sup> Zn		
2	DG167 Pin header	4022B00010 (H)	XX	Brass	SnCe		
1	DG167-5.0-Housing	4022A0YXXA (H)	1	PA66	UL94V-0		
ITEM		NAME OF PART		NO. OF PART	Q'TY	MATERIAL	NOTES
DETAILED LISTS			DFTO DZJ		DATE 06/10/05		
	(INCH)		CHKD		DATE		
	TOLERANCES EXCEPT AS NOTED		MFO		DATE		
			APPVL		DATE		
	MM		MATERIAL :				
	.0 ±		G.E :				
	.00 ±		FINISH :				
	.000 ±		SCALE : 1:1				
	ANGLES ± 1°		THIRD ANGLE PROJECTION				
							
THIRD ANGLE PROJECTION							
				宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD			
		NAME DG167-5.0-XXP-1Y-00A(H)					
		DRAWING NO. DG167-5.0-E02			SIZE A3		REV T7
		/PART NO.			08/28/08		
		DO NOT SCALE DRAWING			SHEET 1		OF 1