



- Notes:
1. Pitch: 3.81mm
  2. Rated voltage/current: UL 300V/10A  
VDE 130V/10A
  3. Operation temperatures: -40°C ~ +105°C
  4. Withstanding Voltage: AC2000V/1Min
  5. Insulation Resistance: 5000M $\Omega$ /DC1000V
  6. Wire Range: 24~18AWG, 1.0mm<sup>2</sup>
  7. Max. Torque Value: 2.04kgf.cm
  8. Undimensioned Tolerances:

Pitch range in mm			Nominal dimension range in mm						
to	over		to	over	to	over	to	over	
6	10	to 24	30	60	100	150	150	150	150
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	±0.05/10	150

4	DG350R-Pin header	4018B00010(H)	XX	Brass	SnCe
3	DG350-Screws	S000001400(H)	XX	Steel	Cr <sup>3+</sup> Zn
2	DG350-Spring	X000000290(H)	XX	Phosphor bronze	Ni plated

SECTION A-A

1	DG340R-3.81-Housing	4016A0YXXA(H)	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DEGSON® 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD					
NAME DG340R-3.81-XXP-1Y-00A(H)					
DRAWING NO. DG340R-3.81-E01					
/PART NO.					
DO NOT SCALE DRAWING					
SHEET 1 OF 1					