



Notes:

1. Pitch: 5.0mm , Poles: XXP
2. Rated voltage/current: UL 300V/8A
VDE 250V/15A
3. Operation temperatures: -40℃~+105℃
4. Withstanding Voltage: AC2500V/1Min
5. Insulation Resistance: 5000MΩ/DC1000V
6. Wire Range: 26~16AWG, 0.2~1.5mm²
7. Undimensioned Tolerances:

Pitch range in mm			Nominal dimension range in mm							
	over 6	over 10	over 30	over 60	over 100	over 150				
to 6	to 10	to 24	to 30	to 60	to 100	to 150				
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10		

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
1		工程变更	Hang	07/27/07
2		商标去掉	LJH	09/04/07
3		品名、料号增加环保标示“(H)”	LJH	12/08/07
4		增加刻字	LJH	02/20/08
5		按钮材质由PA66变更为POM	WLM	04/20/09
6	10-0322	增加VDE刻字及修改参数	ZXX	09/28/10

5	DG211R-5.0-Pin header	3034B00020 (H)	XX	Brass	SnCe Plated
4	DG211V/R-5.0-Spring	X000001360 (H)	XX	Stainless steel	
3	DG211V/R-5.0-Button	3034D0Y01A (H)	XX	POM	UL94HB
2	DG211V/R-5.0-Cover	3034C0Y01A (H)	1	PA66	UL94V-0
1	DG211V/R-5.0-Housing	3034A0Y01A (H)	XX	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
TOLERANCES EXCEPT AS NOTED		DFTO Alon	DATE 05/18/06	<div>DEGSON 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD</div> <div>NAME DG211R-5.0-XXP-1Y-00A(H)</div> <div>DRAWING NO. DG211R-5.0-E01</div> <div>SIZE A3</div> <div>REV T6 09/28/10</div>	
MM		CHKD	DATE		
TOLERANCES EXCEPT AS NOTED		MFO	DATE		
MM		APPL	DATE		
ANGLES ± 1°		MATERIAL :		G.E :	
THIRD ANGLE PROJECTION		FINISH :		DO NOT SCALE DRAWING	
		SCALE : 1:1		SHEET 1 OF 1	