


SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:	
PART NO: LCB3216-221Y-N				DWG.NO: TE9917920	
CUSTOMER PART NO:				CUST.DWG.NO:	
(1) DIMENSIONS (UNIT: mm) 				A	3.2 ± 0.2 m/m
				B	1.6 ± 0.2 m/m
				C	1.1 ± 0.2 m/m
				D	0.5 ± 0.3 m/m
				E	m/m
				F	m/m
				G	m/m
				H	m/m
				I	m/m
				J	m/m
(2) ELECTRICAL REQUIREMENTS					
Z (Ω)	220 ± 25%	TEST FREQ	100MHz / 100mV		
RDC (Ω)	0.05 (MAX)	TEST FREQ			
IDC (mA)	3000 (MAX)	TEST FREQ			
TEST INSTRUMENTS HP 4338A MILLIOHMMETER HP 4291B RF IMPEDANCE / MATERIAL ANALYZER				APPROVED BY 吳載敏	
				CHECKED BY 張明德	
				DRAWN BY Vicky	

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER :					DATE :				
PART NO: LCB3216-221Y-N					DWG.NO: TE9917920				
CUSTOMER PART NO :					CUST.DWG.NO :				
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)		DIMENSION (UNIT : mm)				
FREQ	100MHz /100mV				A	B	C	D	
SPEC	220 ± 25%	0.05 (MAX)	3000 (MAX)		3.2 ± 0.2	1.6 ± 0.2	1.1 ± 0.2	0.5 ± 0.3	
1	211.1	0.009	OK		3.20	1.60	1.10	0.51	
2	205.6	0.009	OK		3.23	1.63	1.11	0.48	
3	214.2	0.008	OK		3.25	1.62	1.12	0.48	
4	197.4	0.009	OK		3.20	1.63	1.12	0.49	
5	208.3	0.008	OK		3.17	1.59	1.11	0.49	
6	200.3	0.008	OK		3.22	1.62	1.10	0.52	
7	209.0	0.009	OK		3.21	1.61	1.11	0.50	
8	197.3	0.009	OK		3.23	1.61	1.09	0.52	
9	202.6	0.009	OK		3.25	1.62	1.10	0.48	
10	206.5	0.009	OK		3.21	1.63	1.11	0.50	
X	205.2	0.009			3.22	1.62	1.11	0.50	
R	16.9	0.001			0.08	0.04	0.03	0.04	
						APPROVED BY 吳載敏			
						CHECKED BY 張明德			
						DRAWN BY Vicky			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

LCB3216-221Y-N

