



REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE
△		增加VDE刻字及参数	WLM	07/21/08
△	09-0073	修改螺丝材质"Steel"为"Brass"	LJH	10/05/09
△	10-0019	将螺丝由PC2.5B改为TSCB4螺丝	HD	01/26/10
△	10-0115	更新图面	HD	05/11/10
△	10-0143	增加UL刻字及参数	COCO	06/11/10

Notes:

- Rated voltage/current:UL 300V/30A
VDE 500V/32A
- Operation temperatures: -40° C~+105° C
- Withstanding voltage: AC3000V/1Min
- Insulation resistance: 5000MΩ/1000V
- Wire range:26~10AWG, 0.2~4.0mm²
- Torque Max:M3, 5.4kgf.cm
- Undimensioned Tolerances:

Pitch range in mm			Nominal dimension range in mm							
	over 6	over 10		over 30	over 60	over 100	over 150			
to 6	to 10	to 24	to 30	to 60	to 100	to 150				
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10		

5	TSCB4-Screw △	S000002530 (H)	4	△ Brass	Ni Plate
4	PCKK4-Short Contact	6122B00020 (H)	1	Copper	SnCe Plate
3	PCKK4- Long Contact	6122B00010 (H)	1	Copper	SnCe Plate
2	PCKK4-Brass Cage	X000001840 (H)	4	Brass	Ni Plate
1	PCKK4-00A Housing	6122A0Y01A (H)	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DETAILED LIST		<div> <div> <div>MM (INCH)</div> <div>TOLERANCES EXCEPT AS NOTED</div> <div> <div>MM</div> <div>.0 ±</div> <div>.00 ±</div> <div>.000 ±</div> </div> <div>±</div> </div> <div> <div>ANGLES ± 1°</div> <div>THIRD ANGLE PROJECTION</div> </div> </div> <div> <div>DFTO LINDA</div> <div>CHKD</div> <div>MFO</div> <div>APPVL</div> <div>G.E :</div> <div>FINISH :</div> <div>SCALE : 1:1</div> </div> <div> <div>DATE 01/05/'08</div> <div>DATE</div> <div>DATE</div> <div>DATE</div> <div>MATERIAL :</div> </div>			
NAME		<div> <div>DEGSON®</div> <div>宁波高正电子有限公司</div> <div>DEGSON ELECTRONICS CO., LTD</div> </div> <div>PCKK4-01P-1Y-00A (H)</div>			
DRAWING NO. PCKK4-E01		SIZE A3		REV T5 06/11/10	
DO NOT SCALE DRAWING		SHEET 1		OF 1	