



Notes:

1. Pitch:21.8, Ploes:10P
2. Rated voltage/Current:VDE 800V 76A
3. Operation temperatures:-40℃~+85℃
4. Withstanding Voltage:AC3000V/1Min
5. Insulation Resistance:5000M $\Omega$ /DC1000V
6. Wire Range:2x(4-16)mm<sup>2</sup>
7. Max. Torque Value:M8.0, 35.7Kgf.cm(31.01Lb.in).

3	DG16T" + "Screw	S000003440 (H)	10	Steel	Cr <sup>3+</sup> Zn
2	DG16T-Current carrier	X000004470 (H)	10	Steel	Cr <sup>3+</sup> Zn

1	DG16T-Housing	2045A0710A (H)	1	PC	UL94V-2
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES
DETACHED LISTS	<div>← MM (INCH) →</div>		DFTO <i>Apple</i>	DATE 10/10/09*	<div> 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD</div>
	TOLERANCES EXCEPT AS NOTED		CHKD	DATE	
			MFO	DATE	
			APPVL	DATE	
	<div>MM</div> <div>0-30 ±0.25 30-60 ±0.3 60-100 ±0.5 100-150 ±0.7 over150 ±1.0</div> <div>± ± ± ±</div>		MATERIAL :		NAME DG16T-10P-17-100A (H)
	ANGLES ± 1°		G.E :		
	<div></div> <div>THIRD ANGLE PROJECTION</div>		FINISH :		
	SCALE : 1:1		DO NOT SCALE DRAWING		SHEET 1 OF 1