



REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
1		增加UL刻字	CSX	03/21/07
2		品名、料号增加环保标识“(H)”	YeJ	12/08/07

- Notes:
1. Pitch:7.62mm ,Poles:2-26P
  2. Rated current:15A
  3. Rated voltage:300V
  4. Operation temperatures:-40° C~+105° C
  5. Insulation Withstand Voltage:AC2000V/Min
  6. Insulation Resistance:500MΩ /DC500V
  7. Wire Range:22~14AWG
  8. Max.Torque Value:5.1kgf.cm
  9. Undimensioned Tolerances:

Pitch range in mm			Nominal dimension range in mm						
to	over	to	to	over	over	over	over	over	
6	6	10	10	30	60	100	150	150	∩
to 6	to 10	to 24	to 30	to 60	to 100	to 150	to 150	to 150	∇
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	±0.05/0	

4	DG28-Cover	5006C07XXA(H)	1	PC	
3	DG28S Pin header	5006B00040(H)	XX	Brass	SnCe plated
2	M3*6(6*6)bright Screws	S000000450(H)	XX	Steel	Ni plated

1	DG28-B-本体	5006A0YXXA(H)	1	PA66+23%GF	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES
TOLERANCES EXCEPT AS NOTED		DFTO Zhuwm	DATE 03/13/06	DEGSON® 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD	
MM (INCH)		CHKD	DATE		
.0 ±		MFO	DATE		
.00 ±		APPVL	DATE		
.000 ±		MATERIAL :		NAME DG28S-B-XXP-1Y-00A(H)	
ANGLES ± 1°		G.E :		DRAWING NO. DG28S-E02	
THIRD ANGLE PROJECTION		FINISH :		/PART NO.	
		SCALE : 1:1		DO NOT SCALE DRAWING	
				SHEET 1 OF 1	

SIZE A3	REV T2
12/08/07	