



SECTION A-A

NOTES:

1. Pitch: 8.25mm, Poles: 2P-20P;
2. Rated: 300V/20A;
3. Temp. Range:  $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$ ;
4. Withstand Voltage: AC2000V/1Min;
5. Wire Range: 22-12AWG;
6. Insulation Resistance:  $500\text{M}\Omega$  /DC500V;
7. Max. Torque Value: 5.1Kgf.cm.
8. Undimensioned Tolerances:

Pitch range in mm			Nominal dimension range in mm					Tolerance
to 6	over 6 to 10	over 10 to 24	to 6	over 6 to 30	over 30 to 90	over 90 to 200	over 200 to 480	
±0.10	±0.15	±0.25	±0.1	±0.2	±0.3	±0.5	±0.7	0.05

3	DG36S Pin header	5011B00010 (H)	XX	Brass	SnCe
2	M3*6 (6.5*6.5) bright screws	S000000490 (H)	XX	Steel	Ni plated

1	DG36S-B-Housing	5011A0YXXA(H)	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
 MM (INCH) TOLF .0 ± .00 ±	DFTD CHKD MFD APPVL ± ±	DATE DATE DATE DATE	 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD		
NAME			DG36S-B-XXP-1Y-00A(H)		
DRAWING NO.				SIZE	REV
/PART NO.				A3	
DO NOT SCALE DRAWING				SHEET	OF
2				1	