



- Notes:
- 1. Pitch:10.0mm Pole:2-24P
  - 2. Rated current:20A
  - 3. Rated voltage:300V
  - 4. Operation temperatures:-40℃~+105℃
  - 5. Withstanding Voltage:AC2000V/1Min
  - 6. Insulation Resistance:500MΩ /DC500V
  - 7. Wire Range:22~12AWG
  - 8. Max. Torque Value: 12.24kgf.cm.
  - 9. Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm						
	over 6 to 10	over 10 to 24	over 30 to 60	over 60 to 100	over 100 to 150	over 150 to 200		
	±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
1		出脚尺寸由5.00±0.2变更到4.65±0.3	CSX	06/16/05
2		将出脚和高度尺寸公差都改为±0.3	wyh	09/10/05
3		图面更新	HW	06/12/06
4		增加UL刻字	Ye.j	01/30/07
5		品名、料号增加环保标识“(H)”	Ye.j	12/08/07

1	DG55R-A Housing	5004M0YXXA(H)	1	PA66	UL94V-0	
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES	
DETACHED LISTS	<div>MM (INCH)</div>		DFTO WSJ	DATE 11/03/03"		
	TOLERANCES EXCEPT AS NOTED		CHKD	DATE		
			MFO	DATE		
			APPVL	DATE		
	<div>MM</div> <div>.0 ±</div> <div>.00 ±</div> <div>.000 ±</div>		<div>±</div> <div>±</div> <div>±</div>		<div> 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD</div> <div>NAME DG55R-A-XXP-1Y-00A(H)</div> <div>DRAWING NO. DG55R-E03</div> <div>/PART NO.</div> <div>SIZE A3</div> <div>REV T5 12/08/07"</div>	
	ANGLES ± 1°		G.E :			
	<div></div> <div>THIRD ANGLE PROJECTION</div>		FINISH :			
			SCALE : 1:1			
			DO NOT SCALE DRAWING			
			SHEET 1 OF 1			

3	4*8 bright Screw	S000000570 (H)	XX	Steel	Ni Plated
2	DG45R Pin header	5003B00060 (H)	XX	Brass	SnCe Plated