REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
1		品名、料号增加环保标示"(H)"	LJH	12/11/07'
2		增加UL、VDE刻字	LJH	03/20/08'
3		修改品名料号中"Y"为"C"	LJH	04/06/09'
4		增加限位结构	CW	05/18/09
5	10-0140	取消铆接工艺,直接焊接	Gary Huang	05/21/10'



Notes:

1. Operation temperatures:-40° C～+105° C
2. Withstanding Voltage:AC3000V/1Min
3. Insulation Resistance:5000MΩ/1000V
4. Wire Range:28～12AWG, 2.5mm²
5. Undimensioned Tolerances:

Pitch range in mm			Naminal dimension range in mm					—
to 6	over 6 to 10	over 10 to 24	to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	⌒ / ▱
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

将载流体与接地体用锡焊接.5

ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES
4	WS2.5-PE-Ground Pin	6032B00010(H)	1	Copper	SnCe
3	DG242-5.0-Shrapnel	X000000990(H)	2	Stainless steel	
2	WS2.5-Current Carrier	6027B00010(H)	1	Copper	SnCe
1	WS2.5-PE-Housing	6032A0C01A(H) 3	1	PA66	UL94V-0

DETACHED LISTS

MM (INCH)

TOLERANCES EXCEPT AS NOTED

MM
.0 ±
.00 ±
.000 ±

ANGLES ± 1°

THIRD ANGLE PROJECTION

DFTD LYK DATE 07/15/07'
CHKD DATE
MFG DATE
APPVL DATE

MATERIAL :

G.E :

FINISH :

SCALE : 1:1

DEGSON® 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD

NAME (黄绿混色)3

WS2.5-PE-01P-1C-00A(H)

DRAWING NO. WS2.5-PE-E01

/PART NO.

SIZE A3

REV T5 05/21/10'

DO NOT SCALE DRAWING

SHEET 1 OF 1