D1RFRD006

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
1		料号变更:由S000001370变更为S000000980	Yangys	01.12.07"
2		品名、料号增加环保标示"(H)"	LJH	12/11/07"
3		增加VDE,CE刻字	Zengy	11/19/08"

Notes:
1. Pitch:7.5mm ,Poles:2-12P
2. Rated voltage/current:UL 300V/15A
   VDE 400V/10A
3. Operation temperatures:-40℃～+105℃
4. Withstanding Voltage:AC2000V/1Min
5. Insulation Resistance:5000MΩ/DC1000V
6. Wire Range:28～12AWG,1～2.5mm²
7. Max.Torque Value:M2.5,4.08kgf.cm
8. Undimensioned Tolerances:

Pitch range in mm			Naminal dimension range in mm					—
to 6	over 6 to 10	over 10 to 24	to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	⌒ / ▱
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10











SECTION A-A



ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES
3	2EDGK Screw"-"M2.5	S000000980(H)	XX	Steel	$Cr^{3+}Zn$
2	DG128 CAGE	X000000020(H)	XX	Brass	Ni plated
1	2EDGKA-7.5 housing	1052A0YXXA(H)	1	PA66	UL94V-0
5	2EDGKA-7.5 Cover	1052C0YXXA(H)	1	PA66	UL94V-0
4	2EDGKA-Clamp	1028B00010(H)	XX	Phosphor bronze	Ni plated

DETACHED LISTS

MM (INCH)
TOLERANCES EXCEPT AS NOTED
MM .0 ± ± .00 ± ± .000 ± ±
ANGLES ± 1°
THIRD ANGLE PROJECTION

DFTO Zhuwm	DATE 09/27/06"
CHKD	DATE
MFO	DATE
APPVL	DATE
MATERIAL :	
G.E :	
FINISH :	
SCALE : 1:1	

DEGSON® 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD

NAME 2EDGKB-7.5-XXP-1Y-00A(H)

DRAWING NO. 2EDGKB-7.5-E01 /PART NO.

SIZE A3 | REV T3 11/19/08"

DO NOT SCALE DRAWING | SHEET 1 OF 1

8 7 6 5 4 3 2 1

H G F E D C B A