


REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE
1		图面更新	Hang	05/07/06
2		修改总长	CSX	09/07/06
3		图面更新	WF	01/31/07
4		增加CQC刻字	WLM	01/09/09
5	10-0359	增加VDE刻字及修改参数	ZXX	10/21/10



- Notes:
- Pitch: 7.62mm , Poles: XXP
  - Rated voltage/current: UL 300V/10A  
VDE 450V/15A
  - Operation temperatures: -40°C~+105°C
  - Withstanding Voltage: AC2000V/1Min
  - Insulation Resistance: 5000MΩ/DC1000V
  - Wire Range: 22~16AWG, 0.2~1.5mm²
  - Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm						
to 6	over 6 to 10	over 10 to 24	to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	∩
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	◇

6	DG142 Spring	X000000130 (H)	XX	Stainless Steel	
5	DG142V Pin header	3003B00010 (H)	XX	Brass	SnCe plated
4	DG142 Clapboard	3003H0Y01A (H)	XX-1	PA66	UL94V-0
3	DG142V-5.08 Button	3003D0501A (H)	XX	PA66	UL94V-0
2	DG142V-5.08 Cover	3003C0Y01A (H)	1	PA66	UL94V-0

1	DG142V-5.08 Housing	3003A0Y01A (H)	XX	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
TOLERANCES EXCEPT AS NOTED		DFTO Home	DATE 02/15/06	DEGSON® 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD	
MM (INCH)		CHKD	DATE		
TOLERANCES EXCEPT AS NOTED		MFO	DATE		
TOLERANCES EXCEPT AS NOTED		APPVL	DATE		
ANGLES ± 1°		G.E :		NAME	
THIRD ANGLE PROJECTION		FINISH :		DG142V-7.62-XXP-1Y-00A(H)	
SCALE : 1:1		DO NOT SCALE DRAWING		DRAWING NO. DG142V-7.62-E03	
				/PART NO.	
				SIZE A3	
				REV T6 10/21/10	
				SHEET 1 OF 1	