


REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
△		Drawing emend	CSX	05/06/06
△		品名、料号增加环保标示“(H)”	LJH	12/11/07
△		增加VDE刻字	WLM	11/04/08
△		“4-24P”修改为“4-48P”	WLM	01/09/09

- Notes:
1. Pitch: 5.08mm , poles: 4-48P (Even) △
  2. Rated voltage/current: UL 300V/15A  
VDE 320V/10A
  3. Operation temperatures: -40°C ~ +105°C
  4. Withstanding Voltage: AC2000V/1Min
  5. Insulation Resistance: 5000MΩ/DC1000V
  6. Undimensioned Tolerances:

Pitch range in mm				Nominal dimension range in mm				
	over 6	over 10		over 30	over 60	over 100	over 150	
	to 10	to 24		to 30	to 60	to 100	to 150	
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
4	2EDGVT-long pin	1032B00010 (H)	XX	Brass	SnCe
3	2EDGV-pin	1007B00030 (H)	XX	Brass	SnCe
2	2EDGVT-5.08 cover	1056C0YXXA (H)	1	PA66	UL94V-0
1	2EDGVT-5.08 housing	1056A0YXXA (H)	1	PA66	UL94V-0

DETACHED LISTS	MM (INCH)	DFTD Haoyh	DATE 04/12/05	<b>DEGSON</b> 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD	
	TOLERANCES EXCEPT AS NOTED	CHKD	DATE		
		MFO	DATE		
		APPVL	DATE		
	MM	±	NAME		2EDGVT-5.08-XXP-1Y-00A(H)
	.00 ±	±	DRAWING NO. 2EDGVT-5.08-E01		
	.000 ±	±	/PART NO.		
			SIZE A3		
	ANGLES ± 1°	G.E :	REV T4		01/09/09
	THIRD ANGLE PROJECTION	FINISH :	DO NOT SCALE DRAWING		
		SCALE :	SHEET 1 OF 1		