



- Notes:
- 1. Pitch:3.81mm poles:2-16P
 - 2. Rated voltage/current: UL 300V/8A
IEC 160V/8A
 - 3. Insulation resistance: 5000MΩ/DC1000V
 - 4. Withstanding voltage: AC2000V/1Min
 - 5. Wire range: 28-16AWG 1.5mm²
 - 6. Temp. Range: -40° C~+105° C
 - 7 Torque: 4.08kgf.cm
 - 8.Undimensioned Tolerances:

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
09-0135		增加UL刻字及UL参数	GHY	12-06-09

Pitch range in mm		Nominal dimension range in mm						
to	over	to	over	to	over	to	over	
6	6 to 10	10 to 24	30 to 60	60 to 100	100 to 150	150 to 150	150 to 150	—
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

6	2EDG Screw cap	S000000040 (H)	2	Brass	
5	15EDG-“—”Screws	S000001360 (H)	XX	Steel	Cr ³⁺ Zn
4	15EDG-Brass cage	X000000010 (H)	XX	Brass	Ni plated
3	15EDGKR-Pin	1215B00010 (H)	XX	Copper	SnCe plated
2	15EDGK-3.81-Cover	1010C0YXXA (H)	1	PA66	UL94V-0
1	15EDGKRM-3.81-Housing	1216A0YXXA (H)	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES

DETACHED LISTS	<div>← MM (INCH) →</div>		DFTO Zhuwm	DATE 12/14/07*	<div>DEGSON®</div> <div>宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD</div>			
	TOLERANCES EXCEPT AS NOTED		CHKD	DATE				
	<div>MM</div> <div>.0 ± ±</div> <div>.00 ± ±</div> <div>.000 ± ±</div>		MFO	DATE	NAME 15EDGKRP-3.81-XXP-1Y-00A (H)			
			APPVL	DATE				
			MATERIAL :			DRAWING NO. 15EDGKRP-3.81-E01	SIZE A3	REV T1 12/06/09*
	ANGLES ± 1°		G.E :					
	<div></div> <div>THIRD ANGLE PROJECTION</div>		FINISH :		/PART NO.			
			SCALE : 1:1		DO NOT SCALE DRAWING		SHEET 1 OF 1	

8	7	6	5	4	3	2	1
---	---	---	---	---	---	---	---