



- NOTES:
1. Pitch: 5.0mm, Poles: 4-48P (Even)
  2. Rated voltage/current: UL 300V/15A  
VDE 320V/10A
  3. Operation temperatures: -40° C ~ +105° C
  4. Withstanding voltage: AC2000V/1min
  5. Insulation resistance: 5000MΩ/1000V
  6. Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm						
to 6	over 6 to 10	over 10 to 24	to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	Q05/10

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
1		Drawing emend	WF	02/22/06*
2		Drawing emend	CSX	04/27/06*
3		增加UL刻字	CSX	08/31/07*
4		品名、料号增加环保标示“(H)”	LJH	12/11/07*
5		增加VDE刻字	WLM	11/04/08*
6		“4-24P”修改为“4-48P”	WLM	01/09/09*

4	2EDGVT-long pin	1032B00010 (H)	XX	Brass	SnCe
3	2EDGV(A)-pin	1007B00030 (H)	XX	Brass	SnCe
2	2EDGVT-5.0 cover	1032C0YXXA (H)	1	PA66	UL94V-0

1	2EDGVT-5.0 housing	1032A0YXXA (H)	1	PA66	UL94V-0	
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES	
DETACHED LISTS	<div>← MM (INCH) →</div>		DFTO WVP	DATE 09/18/04*		
	TOLERANCES EXCEPT AS NOTED		CHKD	DATE		
			MFO	DATE		
			APPVL	DATE		
			NAME 2EDGVT-5.0-XXP-1Y-00A(H)			
	MATERIAL :					
	ANGLES ± 1°		G.E :		DRAWING NO. 2EDGVT-5.0-E01	
			FINISH :		/PART NO.	
THIRD ANGLE PROJECTION		SCALE :		DO NOT SCALE DRAWING		
				SHEET 1 OF 1		



宁波高正电子有限公司  
DEGSON ELECTRONICS CO., LTD

SIZE  
A3

REV  
T6  
01/09/09\*