

REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

NOTES1:

UL Standard

1.Rated voltage/current : 300V / 8A

2.Withstanding voltage : AC1600V/1Min.

IEC Standard

1.

Pollution degree	2
Overvoltage category	II
Rate impulse voltage(KV)	2.5KV
Rate voltage(V)	250V
Rate current(A)	8A

NOTES2:

1.Dimension shall be interpreted per ASME Y14.5-2009

2.Pitch : 3.5mm, Poles : N=04~48P

3.Operating temperature: -40°C~+130°C

4.Undimensioned tolerances:

Pitch range in mm		Nominal dimension range in mm						0.1/10
TO	Over	Over	Over	Over	Over	Over	Over	
6	6 TO 10	10 TO 24	30 TO 60	60 TO 100	100 TO 150	150 TO 300	300 TO 600	≤
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°

5.RoHS Compliance

15EDGVHB-THR - 3.5 - XXP - 1Y - 10A (H)
(Series No.) (Pitch) (Poles) (Single Pitch) (Color): 1.(Grey)
3.(Black)
5.(Orange)

DETACHED LISTS	PART NO.:	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD			
	APPD:	NAME:			
	CHKD:	15EDGVHB-THR-3.5-XXP-1Y-10A(H)			
	DRFT:	TITLE: CUSTOMER DRAWING		REV	DO
THIRD ANGLE PROJECTION		DRAWING NO.:	SHEET		1/1
		MM (INCH)	DO NOT SCALE DRAWING	SCALE	1:1