



REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
1		品名,料号增加环保标示“(H)”	LJH	12/11/07
2		增加UL,CE刻字	Zengy	09/09/08
3		增加VDE及参数刻字	LJH	02/11/09

- Notes:
- 1. Pitch: 3.81mm, Poles: 4-48P
 - 2. Rated voltage/current: UL 300V/8A
VDE 250V/7A
 - 3. Operation temperatures: -40℃ ~ +105℃
 - 4. Withstanding Voltage: AC2000V/1Min
 - 5. Insulation Resistance: 5000MΩ/DC1000V
 - 6. Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm						
to 6	over 6 to 10	over 10 to 24	to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	—
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

5	2EDG-Screw-Cap	S000000040 (H)	4	Brass	
4	15EDGRH-3.81-Cover	1064C0YXXA (H)	1	PA66	UL94V-0
3	15EDGRH-PIN	1063B00020 (H)	XX/2	Brass	SnCe
2	15EDGR-PIN	1003B00010 (H)	XX/2	Brass	SnCe

1	15EDGRHM-3.81-HOUSING	1080A0YXXA (H)	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DETAILED LISTS		DATE 08/02/06	DEGSON® 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD		
MM (INCH)		DATE	NAME		
TOLERANCES EXCEPT AS NOTED		DATE	15EDGRHM-3.81-XXP-1Y-00A (H)		
MM		DATE	DRAWING NO. 15EDGRHM-E01		
.0 ±			/PART NO.		
.00 ±			DO NOT SCALE DRAWING		
.000 ±			SHEET 1 OF 1		
ANGLES ± 1°					
THIRD ANGLE PROJECTION					